

Food Preparation Machines
Made in Sweden

RG-350 Vegetable Preparation Machine

- Slices, dices, shreds, grates, cuts julienne and potato chips/French fries.
- Processes fruit, vegetables, dry bread, cheese, nuts, mushrooms, etc.
- Robust design made for commercial use and long life.
- High capacity. Processes up to 1200 portions/day, 30 kg/minute with feed hopper and 12 kg/minute with manual feeder ergo loop.





A machine with two faces

RG-350 is one of HALLDEs strongest and most efficient vegetable preparation machines. It has two different types of feeders - manual feeder ergo loop and feed hopper. The larger 215 mm cutting tools enables larger volumes to be processed.



The manual feeder ergo loop is equipped with HALLDE Power Link which gives you a leverage effect from the pusher plate. This results in almost 50 percent less manual power. For a better working posture, the pusher plate has a looped designed handle, HALLDE ErgoLoop, which means you can work with both your left and right hands. The leaning design means that the feed cylinder is always positioned at the right angle - the machine is easy to top up. We recommend our vertically adjustable machine table to ensure you always work at the right height when using the machine. Especially when using the feed hopper.



Highest possible reliability

The powerful motor has a high starting and running torque and powers the directdriven cutting tool. No belts or intermediate connections. The power from the motor goes via a maintenance free gear drive. This makes the RG-350 an exceptionally reliable machine - irrespective of the products you are preparing.



Cutting tools with complete register

You choose the cutting tool you need to make you even more efficient in the kitchen. The RG-350 slices, dices, shreds, grates, cuts juliennes and crimping slices everything from firm to soft products. The large 215 mm cutting tools enables faster processing. The knife blades and grating plates are replaceable. As a result you do not need to buy new cutting tools.



Safe and quick top ups

The machine stops as soon as the pusher plate is swung aside. When it is swung back the machine restarts and you can continue working. All thanks to an automatic start and stop function. A clear advantage, particularly when larger volumes are involved. At even larger volumes use the feed hopper. Potatoes, onion, apples etc. can be bucket fed into the feed hopper. This shortens the process and no manual force is needed.



If the feed cylinder is removed when the pusher plate is swung aside, the power is cut. Thanks to this double security there is no risk of the machine starting with an unprotected cutting tool.



The RG-350 is manufactured solely from hygiene certified material. The machine has smooth surfaces, rounded edges and has no unnecessary recesses where food might penetrate and get stuck.

Easy cleaning

For quick cleaning are all loose parts simple to remove for easy rinsing of the machine. The pusher plate, feed hopper and feed cylinder are removable and can be cleaned under running water.

Only the best material

Machine base, feed cylinder and pusher plate are all made of robust metal. Only top quality stainless steel is used to manufacture the cutting tool knife blades.



Always perfect cutting results

The rotation speed of the cutting tools is optimised for cutting fine and even slices as efficiently as possible. The knife blades are purposely sharpened to avoid inertia or the edge breaking off.













Brush

Wall Rack

Feed Hopper Machine Table **Container Trolley**

Top quality cutting tools for any cut and optimal results

RG-350 Cutting Tool Guide



Slicer (stainless steel) 0.5, 1, 1.5, 2, 3, 4, 5, 6, 7, 8, 9, 10 mm.

- Slices firm and soft products, such as root vegetables, bell pepper, onion, leek, cucumber, tomato, apple, citrus fruit, bananas, mushrooms, etc.
- Shreds lettuce and cabbage.
- Chops onions in combination with dicing grid.
- Dices in combination with suitable dicing grid.





Standard Slicer

- Slices firm products such as root vegetables.
- Dices in combination with a suitable dicing grid.





Fine Cut Slicer 14, 20 mm.

• The same advantages as "Slicer".





Crimping Slicer (stainless steel) 2, 3, 4, 5, 6 mm.

• For ripple slicing of beetroot, cucumber, carrots, etc.





Julienne Cutter (stainless steel)

2x2, 2x6, 3x3, 4x4, 6x6, 8x8, 10x10 mm.

- Cuts julienne potatoes and carrots for soups, cucumber for salads, etc.
- · Julienne potatoes to curved French fries.





Dicing Cutter

12.5 mm.

 Dices root vegetables, potatoes, cabbage in combination with dicing grid.





Dicing Grid

6x6, 8x8, 10x10, 12x12, 15x15, 20x20, 25x25 mm.

 Dices root vegetables, fruit, potatoes, cabbage, swedes, carrots, cucumbers, apples, etc. in combination with a suitable slicer.





French Fry Grid

 Cuts potatoes to streight French Fries in combination with a fine cut slicer.





Raw Food Grater/Shredder (stainless steel)

1.5, 2, 3, 4.5, 6, 8, 10 mm.

- Grates carrots and cabbage for raw salad.
- Grates nut, almonds and dry bread.
- Grates cheese for pizza and gratin.
- Shreds cabbage/white cabbage.





Fine Grater/ Extra Fine Grater/ Hard Cheese Grater (stainless steel)

- Grates root vegetables, dry bread, cheese etc.
- Fine Grater grates raw potatoes for potato pancakes.
- Extra Fine Grater grates radish, dry bread, etc.
- Hard Cheese Grater is perfect for cheese such as parmesan.





Soft Dicing Set 8x8x8, 10x10x10, 12x12x12, 15x15x15 mm

 Combination to dice soft products like tomatoes, onion, pepper, bananas, kiwi, strawberries etc.





© AB Hällde Maskiner 2014













Food Preparation Machines Made in Sweden

RG-350 Vegetable Preparation Machine

- Choice of two different feeders Manual Feeder Ergo Loop or Feed Hopper for continuous feeding.
- Direct driven cutting tools from a strong heavy duty motor with planetary gear transmission.
- "HALLDE PowerLink" provide a leverage effect on the pusher plate which reduces the manual pressure needed to about half.
- "HALLDE ErgoLoop" enables the user to use both hands when operating the machine.
- Large cutting tools with a diameter of 215 mm enable larger volumes to be processes faster.

Machine

- Motor: 0.75 kW. One-speed. 110-120 V, single phase, 50-60 Hz. 220 V, single phase, 60 Hz. 230 V, single phase, 50 Hz. 230 V, three phase, 50 Hz. 400 V, three phase, 50 Hz.
- Transmission: Planetary gearing.
- Safety system: Two safety switches.
- Degree of protection machine: IP44.
- Degree of protection push buttons: IP65.
- Power supply socket: Earthed, single phase,
 10 A alternatively earthed, three phase,
 10 A slow-blow.
- Fuse: 10 A, delayed action fuse.
- Sound level LpA (EN31201): 73 dBA.
- Magnetic field: Less than 0.4 microtesla.

Materials

- Machine housing: Anodized or polished aluminium alloy.
- Cutting tool discs: Stainless Steel / Aluminium alloy.
- Cutting tool knife blades: Stainless knife steel.
- Machine table: Stainless steel. Container: Polycarbonate.

Feeder

- Feed cylinder: Volume 5.7 litre. Height 180 mm. Diameter 200 mm.
 One fixed internal support wall 62 mm wide.
- Feed tube with internal diameter 59 mm.
- Manual Feeder with "HALLDE ErgoLoop" handle and "HALLDE PowerLink" lever system.
- Feed hopper: Volume ca 23 litre. Height 350 mm. Diameter 420 mm.

Cutting tools

• Diameter: 215 mm. • Speed: 360 rpm (50 Hz), 430 rpm (60 Hz).

Type of preparation

- Slices, dices, grates, shreds, cuts julienne and crimping slices.
- Processes vegetables, fruit, dry bread, cheese, nuts, mushrooms, etc.

Users


 Restaurants, shop kitchens, diet kitchens, retirement homes, hospitals, schools, fast food outlets, catering, day care centers, pizzerias, ships, central kitchens, institution kitchens, etc.

Net weights

- Machinebase: 26 kg.
- Manual push feeder: 6 kg.
- Feed hopper: 7.5 kg.
- Cutting plates: 1 kg.

Standards

- EN 1678+A1:2010. Following the provisions of Directive 2006/42/EC, 2006/95/EC, 2004/108/EC.
- \bullet RoHS 2002/95/EC $\,\bullet$ NSF/ANSI Standard 8.



540





