



Ergonomics in all stages

The leaning design means that the feed cylinder is always positioned at the right angle – the machine is easy to top up. Using HALLDE Power Link you get a leverage effect from the pusher plate. The result is that you need almost 50 percent less manual power. For a better working posture, the pusher plate has a looped designed handle, HALLDE ErgoLoop, which means you can work with both your left and right hands. We recommend our vertically adjustable machine table to ensure you always work at the right height when using the machine.



Highest possible reliability

The powerful motor has a high starting and running torque and powers the direct-driven cutting tool. No belts or intermediate connections. The power from the motor goes via a maintenance free gear drive. This makes the RG-250 an exceptionally reliable machine – irrespective of the products you are preparing.



Safe and quick top ups

Thanks to the automatic start and stop function the machine stops as soon as the pusher plate is swung aside. When it is swung back the machine restarts and you can continue working. The RG-250 also has a full moon cylinder that can hold larger quantities and whole products. Features like these are a clear advantage, particularly when larger volumes are involved.



Cutting tools with complete register

Our wide range of cutting tools means the RG-250 can handle every conceivable task. You choose the cutting tool you need to make you even more efficient in the kitchen. The RG-250 slices, dices, shreds, grates, cuts juliennes and crimping slices – everything from firm to soft products. The knife blades and grating plates are replaceable. As a result you do not need to buy new cutting tools.



If the feed cylinder is removed the power is cut. Thanks to this double security there is no risk of the machine starting with an unprotected cutting tool.



Always perfect cutting results

The rotation speed of the cutting tools is optimised for cutting fine and even slices as efficiently as possible. The knife blades are purposely sharpened to avoid inertia or the edge breaking off.



Developed for the best hygiene

The RG-250 is manufactured solely from hygiene certified material. The machine has smooth surfaces, rounded edges and has no unnecessary recesses where food might penetrate and get stuck.



For quick cleaning are all loose parts simple to remove for easy rinsing of the machine. The pusher plate and feed cylinder are removable and can be cleaned under running water.



Only the best material

Machine base, feed cylinder and pusher plate are all made of robust metal. Only top quality stainless steel is used to manufacture the cutting tool knife blades.



Lightweight and easy to move

The relatively small size of the machine gives several advantages. It doesn't take up a lot of space in the kitchen. And it is easy to move, something which is helped by the generously sized handle on the back.





Machine Table



Container Trolley



Wall Rack



Top quality cutting tools for any cut and optimal results

RG-250 Cutting Tool Guide



Slicer (stainless steel) 0.5, 1, 1.5, 2, 3, 4, 5, 6, 7, 8, 9, 10 mm.

- Slices firm and soft products, such as root vegetables, bell pepper, onion, leek, cucumber, tomato, apple, citrus fruit, bananas, mushrooms, etc.
- Shreds lettuce and cabbage.
- Chops onions in combination with dicing grid.
- Dices in combination with suitable dicing grid.





Standard Slicer 20 mm.

- Slices firm products such as root vegetables.
- Dices in combination with a suitable dicing grid.





Fine Cut Slicer

• The same advantages as "Slicer".





Crimping Slicer (stainless steel) 2, 3, 4, 5, 6 mm.

• For ripple slicing of beetroot, cucumber, carrots, etc.





Julienne Cutter (stainless steel) 2x2, 2x6, 3x3, 4x4, 6x6

 Cuts julienne potatoes and carrots for soups, cucumber for salads, etc.





• Julienne potatoes to curved French fries.



Dicing Cutter 12.5 mm.

 Dices root vegetables, potatoes, cabbage in combination with dicing grid.





Dicing Grid

6x6, 8x8, 10x10, 12x12, 15x15, 20x20 mm.

 Dices root vegetables, fruit, potatoes, cabbage, swedes, carrots, cucumbers, apples, etc. in combination with a suitable slicer.





French Fry Grid
10 mm.

 Cuts potatoes to streight French Fries in combination with a fine cut slicer.





Grater/Shredder (stainless steel)

1.5, 2, 3, 4.5, 6, 8, 10 mm.

- Grates carrots and cabbage for raw salad.
- Grates nut, almonds and dry bread.
- Grates cheese for pizza and gratin.
- Shreds cabbage/white cabbage.





Fine Grater
Extra Fine Grater
Hard Cheese Grater
(stainless steel)

- Grates root vegetables, dry bread, cheese etc.
- Fine Grater grates raw potatoes for potato pancakes.
- \bullet Extra Fine Grater grates radish, dry bread, etc.
- Hard Cheese Grater is perfect for cheese such as parmesan.





Soft Dicing 8x8x8, 10x10x10,

12X12X12, 15X15X15 mm

 Combination to dice soft products like tomatoes, onion, pepper, bananas, kiwi, strawberries etc.

















Food Preparation Machines Made in Sweden

RG-250 Vegetable Preparation Machine

- Large full moon feed cylinder that can take most items whole.
- Direct driven cutting tools from a strong heavy duty motor with planetary gear transmission.
- "HALLDE PowerLink" provide a leverage effect on the pusher plate which reduces the manual pressure needed to about half.
- "HALLDE ErgoLoop" enables the user to use both hands when operating the machine.
- · Leaning design and support wall for easy piling of tomatoes, onions etc. for oriented slicing.

Machine

- Motor: 0.55 kW. One-speed. 100 V, single phase, 50-60 Hz. 110-120 V, single phase, 60 Hz. 220 V, single phase, 50 Hz. 230-240 V, single phase, 50 Hz. 230 V, three phase, 50 Hz. 400 V, three phase, 50 Hz. 440 V, three phase, 60 Hz.
- Transmission: Planetary gearing.
- Safety system: Two safety switches.
- Degree of protection machine: IP44.
- Degree of protection push buttons: IP65.
- Power supply socket: Earthed, single phase,
 10 A alternatively earthed, three phase,
 16 A.
- Fuse: 10 A, delayed action fuse.
- Sound level LpA (EN31201): 72 dBA.
- Magnetic field: Less than 0.5 microtesla.

Materials

- Machine housing: Anodized or polished aluminium alloy.
- Cutting tool discs: Stainless Steel / Aluminium alloy.
- Cutting tool knife blades: Stainless knife steel.
- Machine table: Stainless steel.
- Container: Polycarbonate.

Feeder

- Feed cylinder, volume 4 litre, height 180 mm, diameter 170 mm.
 One fixed internal support wall 55 mm wide.
- Feed tube with internal diameter 56 mm.
- Pusher plate with "HALLDE ErgoLoop" handle and "HALLDE PowerLink" lever system.

Cutting tools

- Diameter: 185 mm.
- Speed: 350 rpm (50 Hz), 420 rpm (60 Hz).

Type of preparation

- Slices, dices, grates, shreds, cuts julienne and crimping slices.
- Processes vegetables, fruit, dry bread, cheese, nuts, mushrooms, etc.

Users

 Restaurants, shop kitchens, diet kitchens, retirement homes, hospitals, schools, fast food outlets, catering, day care centers, pizzerias, ships, central kitchens, institution kitchens, etc.

Net weights

- Machine: 21 kg.
- Cutting plates: 0.5 kg.

Standards

- EN 1678+A1:2010. Following the provisions of Directive 2006/42/EC, 2006/95/EC, 2004/108/EC.
- RoHS 2002/95/EC NSF/ANSI Standard 8.











